



DESCRIPTION


Reduce wattage by up to 80%. The LED Wall Pack is a perfect complement to the model T® exterior fixture. Using our patent-pending advanced light engine technology and proprietary optics you will get both 100,000 hour life and exceptional illumination. With its powder coat exterior finish, it will deliver years of trouble free service. Light quality and housing color match the model T perfectly. Fast, easy-to-install design.



Wall Pack LED shown in Bronze.

SPECIFICATIONS

Lumens:	6,414	8,298
Wattage:	60	80
Weight:	14.80 lbs.	
Dimensions:	L 14.666" x W 13.531" x H 6.764"	
Listed/Rated:	UL, DLC	
DLC Model #	WP60-UNCG-HMxx WP60-UNCG-MRxx	WP80-UNCG-HMxx WP80-UNCG-MRxx
Color Temp:	5000K	
CRI:	>82	
Line Voltage:	Universal 120-277V	
Power Supply:	Hardwire standard	
Surge Protection:	Integrated 6kV transient voltage protection	
Ambient Operating Temperature:	-40° to 50° C / -40° to 131° F	
Environment:	Wet rated	
Lens:	Clear glass. Type III forward-throw Hammertone reflector.	
Mount:	Standard wall bracket	
Warranty:	10-year Standard Limited	
Manufacturer:	Genesis Energy Technology	



ORDERING INFORMATION

EXAMPLE: **WP80-UNCG-HMBL-SBMSX** Lead times and costs may vary depending on options selected. Consult your sales representative for more information. Standard configuration highlighted in Gray.

WP	UN	CG	HM		SB		
Model	Wattage (Nominal)	Voltage	Optics	Reflector	Fixture Color	Mounting	Motion / Sensor
WP: Wall pack	60: 60W 80: 80W	UN: 120-277V	CG: Clear glass	HM: Hammertone	BL: Black WH: White BZ: Bronze GR: Gray	SB: Standard wall bracket	DD: Dusk to dawn sensor MSC: Motion sensor MSX: no sensor

Specifications subject to change without notice.