



# energybank. OmegaLight® I-Frame 4-Array

## DESCRIPTION

Designed and built in the USA to deliver 100,000 hour life for maintenance-free, exceptional illumination. The OmegaLight is an award-winning, high-performance LED fixture. Constructed of commercially pure aluminum with thermal vias for superior thermal management. Patent-pending thermal management ensures 100,000 hour life expectancy and lumen maintenance. Optimized optics deliver superior quality, glare-free illumination. Proprietary design prevents entry by particulate matter and insects. Fast, easy-to-install design that easily replaces HID, T8 and T5 fluorescent.



## SPECIFICATIONS

<b>Style:</b>	4-array	
<b>Wattage:</b>	200	360
<b>Lumens:</b>	29,448	47,665
<b>Weight: (lbs)</b>	10.40 lbs	
<b>Dimensions:</b>	L 46.102" x H 3.068" x W 15.845"	
<b>Ambient Operating Temperature:</b>	-30° to 50° C / -22° to 122° F	
<b>Color Temp:</b>	5000K	
<b>CRI:</b>	>84	
<b>Line Voltage:</b>	Universal 120-277V standard	
<b>Power Supply:</b>	Hardwire standard. Internal quick connect for other available power supplies.	
<b>Surge Protection:</b>	Integrated 6kV transient voltage protection. Additional 10kA surge protection option.	
<b>Environment:</b>	Damp rated	
<b>Mounting:</b>	10 ft. adjustable hanging cable	
<b>Packaging</b>	Bulk pack standard. 4 pieces per pack.	
<b>Warranty:</b>	10-year Standard Limited	
<b>Listed:</b>	DLC QPL, ETL	
<b>Manufacturer:</b>	Genesis Energy Technology (A wholly-owned subsidiary of Energy Bank Inc.)	

*Specifications subject to change without notice. Longer lead times may apply when ordering options over standard.*



Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC Qualified Products List at [www.designlights.org/search](http://www.designlights.org/search).



## ORDERING INFORMATION

To order, create the part number using the matrix below. **Example: OA436-UNFR-50BL-NSHW-MSX-A10**. Standard configuration highlighted in Gray. Lead times and costs may vary depending on options selected. Consult your sales representative for more information.

To search listing on DLC QPL, enter characters from only the first 5 categories shown below. **Example: OA436-UNFR-50**

OA4	UN	F1	50		NS	HW		BP	A10	
Model	Wattage	Voltage	Optics	Color Temp	Fixture Color	Surge	Power Supply	Controls	Packaging	Hanging Hardware
OA4: OmegaLight	20: 200W	UN: 120-277V	F1: Frosted	50: 5000K	BL: Black	NS: Integrated	HW: Hardwire	MSX: No sensor	BP: Bulk Pack	A10: 10 ft. adj. hanging cable
	36: 360W				WH: White	WS: Add'l 10kA		MS1: 5 min/5hr	1P: Single Pack	
								MS2: 15 min/5 hr		
								MS3: 30 min/5 hr		
								MS4: 5 min/1 hr		
								MS5: 15 min/1 hr		
								MSC: Custom		