

# Flood SB16

## DESCRIPTION


LED Flood lights from energybank are designed to quickly and easily replace existing 1000W HID or fluorescent fixtures. energybank 100,000 hour life light engines incorporate numerous patent-pending features that produce more footcandles with less energy input. Constructed of die-cast aluminum with a durable, textured powdercoat exterior finish. Bronze is standard. 5-year standard limited warranty from OEM on all light engine components.

## SPECIFICATIONS

<b>Lumens:</b>	19,900
<b>Wattage:</b>	150
<b>Weight:</b>	23.000 lbs.
<b>Dimensions:</b>	H 16.625" x W 16.125" x D 7.000"
<b>Listed/Rated:</b>	CSA
<b>Color Temp:</b> 5000K	
<b>CRI:</b> >80	
<b>Line Voltage:</b> Universal 120-277V. 480V option.	
<b>Power Supply:</b> Hardwire standard	
<b>Surge Protection:</b> Integrated 6kV transient voltage protection	
<b>Ambient Operating Temperature:</b> -40° to 45° C / -40° to 113° F	
<b>Environment:</b> Wet rated	
<b>Lens:</b> Clear glass. Type III forward-throw Hammertone reflector.	
<b>Mount:</b> Pole mount, slip-fitter, swivel.	
<b>Warranty:</b> 5-year Standard Limited	
<b>Manufacturer:</b> Genesis Energy Technology	



Flood LED shown in Bronze. Die-cast aluminum housing & hinged front frame. 1/2" coin plugs for conduit & photocell.



## MOUNTING OPTIONS

### Slip-fitter

Adjustable external mount slip-fitter for 2.375" tenon, Bronze.



### Pole Mount

Adjustable pole arm that directly side mounts to a 4" to 6" round pole that does not have a 2.375" tenon, Bronze.



### Swivel

Two-piece wall or flat surface mount swivel bracket, Bronze.



AMERICAN INNOVATION



Designed & Built in USA

## ORDERING INFORMATION

EXAMPLE: **SB16-UNCG-HMBZ-MSXPM** Lead times and costs may vary depending on options selected. Consult your sales representative for more information. Standard configuration highlighted in Gray.

SB	16		CG	HM	BZ		
Model	Wattage (Nominal)	Voltage	Optics	Reflector	Fixture Color	Motion / Sensor	Mounting
<b>SB:</b> Shoe box	<b>16:</b> 150W	<b>UN:</b> 120-277V	<b>CG:</b> Clear glass	<b>HM:</b> Hammertone	<b>BZ:</b> Bronze	<b>MSX:</b> No sensor	<b>PM:</b> Pole mount
		<b>48:</b> 480V					<b>SF:</b> Adjustable slip-fitter
							<b>SM:</b> 2-piece swivel

Specifications subject to change without notice.