

LightSource® Wall Pack



DESCRIPTION

Reduce wattage by up to 80%. The LightSource LED Wall Pack is a perfect complement to the model T[®] exterior fixture. Using our patent-pending advanced light engine technology and proprietary optics, you will get >50,000 hour-life and exceptional illumination. With its powder coat exterior finish, it will deliver years of trouble-free service. Light quality and housing color match the model T[®] perfectly. Fast, easy-to-install design.

SPECIFICATIONS

144	/0	00			
Wattage:	60	80			
Lumens:	6,414	8,298			
Weight (lbs):	14.80				
Dimensions:	L14.67" x W 13.53" x H6.76"				
Ambient Operating Temperature:	-40° to 50° C / -40° to 131° F				
Listed / Rated:	DLC QPL, UL				
DLC Product ID:	PV35ZNRU	PWJHANAC			
Surge Protection:	Integrated 6 kV Transient Voltage Protection				
Color Temperature:	5,000 K				
CRI:	> 82				
Line Voltage:	Universal 120-277 V Standard				
Environment:	Wet Rated				
Mounting:	Standard Wall Bracket				
Optics:	Clear Glass. Type III Forward-Throw Hammertone Reflector				
Power Supply:	Hardwire				
Warranty:	5 - Year Standard Limited				
Manufacturer:	Genesis Energy Technology (A wholly-owned subsidiary of Energy Bank Inc.)				



Wall Pack shown in Bronze

Specifications subject to change without notice.





Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC Qualified Products List at www.designlights.org/search.

LightSource® Wall Pack

Ordering Matrix

To order, create the part number using the matrix below. Example configuration below is highlighted in Gray. Example: WP80-UNCG-HMBL-DDNS-SB

Lead times and costs may vary depending on options selected. Consult your sales representative for details.

WP	80	UN	CG	НМ	BL	DD	NS	SB
Model	Wattage	Voltage	Optics	Reflector	Fixture Color	Controls	Surge	Mounting
WP: LightSource® Wall Pack	60: 60W	UN: 120-277V	CG : Clear Glass	HM: Hammertone	BL: Black	DD: Dusk to Dawn Sensor	NS: No Additional Surge Protection	SB: Standard Wall Bracket
	80: 80W				WH: White	MSC: Custom Motion Settings	WS: With Additional Surge Protection	
					BZ: Bronze	MSX: No Control		
					GR: Gray			

