

LED Flood SB16



DESCRIPTION

LED Flood Lights from energybank are designed to quickly and easily replace existing 1000 W HID or fluorescent fixtures. energybank's >50,000-hour life light engines incorporate numerous patent-pending features that produce more foot candles with less energy input. Constructed of die-case aluminum with a durable, textured powder-coat exterior finish. Bronze is standard. 5-year standard limited warranty from OEM on all light engine components.

SPECIFICATIONS

Style:	LED Flood				
-	LED Flood				
Wattage:	150 W				
Lumens:	19,900				
Weight (lbs):	23.00				
Dimensions:	H 16.63 x W 16.13 x D 7.00				
Ambient Operating Temperature:	-40° to 45° C / -40° to 113° F				
Listed / Rated:	CSA				
Surge Protection:	Integrated 6 kV Transient Voltage Protection				
Color Temperature:	5,000 K				
CRI:	>80				
Line Voltage:	Universal 120-277 V. 480 V Option Available				
Environment:	Wet Rated				
Hanging Hardware:	Pole Mount, Slip-Fitter, Swivel				
Optics:	Clear Glass. Type III Forward-Throw Hammertone Reflector				
Power Supply:	Hardwire Standard				
Warranty:	5 - Year Standard Limited				
Manufacturer:	Genesis Energy Technology (A wholly-owned subsidiary of Energy Bank Inc.)				

LED Flood shown in Bronze. Die-cast aluminum housing & hinged front frame. 1/2" Coin Plugs for conduit and photocell.





Specifications subject to change without notice.

Mounting Options



Pole Mount (PM)

Adjustable pole arm that directly side mounts to a 4" to 6" round pole that does not have a 2.375" tenon, Bronze



Swivel (SM)

Two-piece wall or flat surface mount swivel bracket, Bronze.



Slip-Fitter (SF)

Adjustable external mount slip-fitter for 2.375" tenon, Bronze



Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC Qualified Products List at www.designlights.org/search.

LED Flood SB16

Ordering Matrix

To order, create the part number using the matrix below. Example configuration highlighted in Gray.

Example: SB16-150-UNCG-HMBZ-NNN

Lead times and costs may vary depending on options selected. Consult your sales representative for details.

SB16	150	UN	CG	НМ	BZ	NNN
Model	Wattage	Voltage	Optics	Reflector	Fixture Color	Controls
SB16: Shoe box	150: 150 W	UN: 120-277V	CG: Clear Glass	HM: Hammertone	BZ: Bronze	NNN: No Control
		48: 480V			CC: ¹ Custom Color	ANN: Ambient Sensor

¹ See Factory for pricing on additional color options.